

The TH114

Electronic Non-Programmable Thermostat

PHONE 360.693.2505
FAX 360.694.8668
WEB www.cadetco.com



Best Choice Non-Programmable – Large Areas

General Information:

The TH114-A-240D electronic thermostat provides precise temperature control using a proportional integral adaptive microprocessor. The slim design, backlit display, and push button access make this a premium choice for a non-programmable thermostat. This double pole (4 wire) model thermostat is recommended for both 240 and 208 volt (line voltage) baseboard and in-wall heater applications. Ambient setpoint range: 40°F to 86°F (5°C to 30°C).

Architectural Information:

The electronic thermostat shall be UL and CSA listed. The thermostat shall have LED indication of status of heater. The control shall be capable of switching loads of 16 amps at 240 VAC. Minimum load requirement 2 amps. Unit shall include thermistor and microprocessor. Vented housing shall be white and made of flame retardant high impact plastic with two mounting screws provided. No batteries shall be required for operation.

Ordering Information: Available in white.

Carton Details

Product

DIMENSIONS | 2.76"W x 4.9"H x .9"D

Single Carton

DIMENSIONS | 3.5"W x 5.5"H x 2.25"D

Case

DIMENSIONS | 13"W x 10.5"H x 13.5"D

— UPC Code —

Part#	Model#	Description	Wt./Lbs	Case Qty
027418 08162 9	TH114-A-240-D	Wholesale Boxed Electronic Non-Programmable DP 16A 240V/208V	1	10



Learn more about
The TH114
Scan It Now!



TH114A-240D