

DESCRIPTION

The DSH Downspout Hanger Kit is the recommended method of providing support and abrasion protection for deicing heater cable in roof gutter downspouts. This kit contains materials for two complete downspout hangers. The DSH Downspout Hanger Kit may be used with all versions of Easy Heat's roof and gutter deicing cables, as well as those made by other manufacturers.

KIT CONTENTS

2	Hanger Wires	4	Hanger Clamp Sections
4	Screws	4	Nuts
2	Protective wraps		

Figure 1





Figure 2 - Cross section view of clamp



WARNING!
POSITIONING IS IMPORTANT
TO PREVENT DAMAGE TO
THE HEATER CABLE.

INSTALLATION PROCEDURES

- Determine the location of the downspout hanger to maximize the support function and reduce stress or abrasion points at the gutter edges.
- Place one piece of protective wrap around both heater cable(s).
- Place the cables and wrap between a pair of hanger clamp sections. Ensure cables are in the clamp wire channels and covered by wrap. See the cross section view in Figure 2.
- Insert screw through the hanger wire eyelet and then through the hanger clamp sections; secure with nut.
- Tighten the nuts and screws to ensure a snug fit. Do not overtighten; cable damage may result.
- Fasten hanger wire with a nail, screw or other means appropriate for the mounting surface.