


THE BEST FLOORS DESERVE IT


The Warm Tiles Elite indoor floor warming system delivers the ultimate comfort for your finest residential and commercial flooring. It features a super thin (3.2 mm (0.125")) heating mat that causes minimal impact on floor height. Mats consist of heating cable interwoven into slim, durable fabric designed to efficiently warm the floor to a comfortable temperature.

Order Standard or Custom Sizes



Standard Configuration

Flexible and easy to install. Available in popular sizes for rectangular areas. See the product selection chart for details and sizing.



Custom Configuration

Available for coverage in rooms with irregular shapes and obstacles. Contact EasyHeat for details and ordering information.

EASYHEAT
Warm Tiles
ELITE

LIMITED WARRANTY

Warm Tiles Elite systems are warranted for 15 years against defects in materials and workmanship.

For more information, visit www.warmtiles.com.
Canada: 1-800-794-3766
US: 1-800-537-4732



©2016 EasyHeat. All rights reserved.
EasyHeat, Inc. is a wholly owned subsidiary of EGS Electrical Group LLC.



40102-201 rev. 3



EASYHEAT
Warm Tiles
ELITE

EASYHEAT

Warm Tiles
ELITE

FEATURES

Super thin mat [3.2 mm (0.125")] means minimal impact on floor height.

Quick installation due to special pre-manufactured mat design, saving cost and time.

High power output [up to 160W/sq m (15W/sq ft)] provides ample heat to quickly and efficiently warm up floors.

Long cold leads [available up to 10.67 meters (35 feet)] provide additional installation flexibility.

Easy to control with EasyHeat programmable or non-programmable thermostats.

Approved for a variety of applications and floor finishes, for the ultimate in versatility and compatibility.

Approved by:
Canadian Standards Association (CSA)
Underwriters Laboratories (UL)

Warm Tiles Elite Mats are designed for today's most popular floors, including:

- Ceramic
- Porcelain
- Terrazzo
- Glass mosaic
- Natural stone and agglomerates
- Engineered wood and laminates
- Marble



SUPER THIN FLOOR WARMING SYSTEM

FAST & EASY INSTALLATION

Using this simple procedure, you can install Warm Tiles Elite in three easy steps:



Apply thin layer of mortar to floor.



Lay down Warm Tiles Elite mat.



Apply thin set and install floor surface.

The floor is installed in one day!

It is important to carefully follow installation instructions provided with the product.

PRODUCT ORDERING SYSTEM

Standard Product Selection for 120 AC Volts ①

Part Number	Length meters	Width meters	Length inches	Width inches	Area in sq m ² (ft ²)	Amps
WTE0400271	1.02	0.69	40	27	0.70 (7.5)	0.9
WTE0400321	1.02	0.81	40	32	0.83 (8.9)	1.0
WTE0400401	1.02	1.02	40	40	1.04 (11.1)	1.3
WTE0400481	1.02	1.22	40	48	1.24 (13.3)	1.6
WTE0480241	1.22	0.61	48	24	0.74 (8.0)	1.0
WTE0480301	1.22	0.76	48	30	0.93 (10.0)	1.2
WTE0480361	1.22	0.91	48	36	1.11 (12.0)	1.4
WTE0480481	1.22	1.22	48	48	1.49 (16.0)	1.9
WTE0600241	1.52	0.61	60	24	0.93 (10.0)	1.2
WTE0600301	1.52	0.76	60	30	1.15 (12.5)	1.5
WTE0600361	1.52	0.91	60	36	1.38 (15.0)	1.8
WTE0600421	1.52	1.07	60	42	1.63 (17.5)	2.3
WTE0600481	1.52	1.22	60	48	1.85 (20.0)	2.2
WTE0600601	1.52	1.52	60	60	2.31 (25.0)	3.2
WTE0720241	1.83	0.61	72	24	1.12 (12.0)	1.5
WTE0720301	1.83	0.76	72	30	1.40 (15.0)	1.8
WTE0720361	1.83	0.91	72	36	1.67 (18.0)	2.1
WTE0720421	1.83	1.07	72	42	1.96 (21.0)	2.5
WTE0720481	1.83	1.22	72	48	2.23 (24.0)	2.7
WTE0720601	1.83	1.52	72	60	2.78 (30.0)	3.6
WTE0840241	2.13	0.61	84	24	1.30 (14.0)	1.7
WTE0840301	2.13	0.76	84	30	1.63 (17.5)	2.2
WTE0840361	2.13	0.91	84	36	1.94 (21.0)	2.4
WTE0840421	2.13	1.07	84	42	2.28 (24.5)	2.8
WTE0840481	2.13	1.22	84	48	2.60 (28.0)	3.4
WTE0840601	2.13	1.52	84	60	3.24 (35.0)	4.0
WTE0960241	2.44	0.61	96	24	1.50 (16.0)	2.0
WTE0960301	2.44	0.76	96	30	1.85 (20.0)	2.6
WTE0960361	2.44	0.91	96	36	2.22 (24.0)	2.8
WTE0960421	2.44	1.07	96	42	2.61 (28.0)	3.5
WTE0960481	2.44	1.22	96	48	2.98 (32.0)	3.8
WTE0960601	2.44	1.52	96	60	3.71 (40.0)	4.6
WTE1080241	2.74	0.61	108	24	1.67 (18.0)	2.3
WTE1080301	2.74	0.76	108	30	2.09 (22.5)	2.6
WTE1080361	2.74	0.91	108	36	2.51 (27.0)	3.1
WTE1080421	2.74	1.07	108	42	2.93 (31.5)	3.7
WTE1080481	2.74	1.22	108	48	3.34 (36.0)	4.1
WTE1080601	2.74	1.52	108	60	4.18 (45.0)	5.3
WTE1180241	3.0	0.61	118	24	1.85 (20.0)	2.3
WTE1180301	3.0	0.76	118	30	2.32 (25.0)	3.2
WTE1180361	3.0	0.91	118	36	2.74 (29.5)	3.7
WTE1180421	3.0	1.07	118	42	3.16 (34.0)	4.2
WTE1180481	3.0	1.22	118	48	3.62 (39.0)	4.7
WTE1180601	3.0	1.52	118	60	4.55 (49.0)	5.7

① 120 Vac custom mat configurations available. Contact EasyHeat.

PRODUCT ORDERING SYSTEM

Standard Product Selection for 240 AC Volts ②

Part Number	Length meters	Width meters	Length inches	Width inches	Area in sq m ² (ft ²)	Amps
WTE0400272	1.02	0.69	40	27	0.70 (7.5)	0.5
WTE0400322	1.02	0.81	40	32	0.83 (8.9)	0.6
WTE0400402	1.02	1.02	40	40	1.04 (11.1)	0.7
WTE0400482	1.02	1.22	40	48	1.24 (13.3)	0.7
WTE0480242	1.22	0.61	48	24	0.74 (8.0)	0.5
WTE0480302	1.22	0.76	48	30	0.93 (10.0)	0.6
WTE0480362	1.22	0.91	48	36	1.11 (12.0)	0.7
WTE0480482	1.22	1.22	48	48	1.49 (16.0)	0.9
WTE0600242	1.52	0.61	60	24	0.93 (10.0)	0.6
WTE0600302	1.52	0.76	60	30	1.15 (12.5)	0.8
WTE0600362	1.52	0.91	60	36	1.38 (15.0)	0.9
WTE0600422	1.52	1.07	60	42	1.63 (17.5)	1.1
WTE0600482	1.52	1.22	60	48	1.85 (20.0)	1.2
WTE0600602	1.52	1.52	60	60	2.31 (25.0)	1.5
WTE0720242	1.83	0.61	72	24	1.12 (12.0)	0.8
WTE0720302	1.83	0.76	72	30	1.40 (15.0)	0.9
WTE0720362	1.83	0.91	72	36	1.67 (18.0)	1.1
WTE0720422	1.83	1.07	72	42	1.96 (21.0)	1.3
WTE0720482	1.83	1.22	72	48	2.23 (24.0)	1.4
WTE0720602	1.83	1.52	72	60	2.78 (30.0)	1.8
WTE0840242	2.13	0.61	84	24	1.30 (14.0)	0.8
WTE0840302	2.13	0.76	84	30	1.63 (17.5)	1.1
WTE0840362	2.13	0.91	84	36	1.94 (21.0)	1.2
WTE0840422	2.13	1.07	84	42	2.28 (24.5)	1.5
WTE0840482	2.13	1.22	84	48	2.60 (28.0)	1.7
WTE0840602	2.13	1.52	84	60	3.24 (35.0)	2.2
WTE0960242	2.44	0.61	96	24	1.50 (16.0)	0.9
WTE0960302	2.44	0.76	96	30	1.85 (20.0)	1.2
WTE0960362	2.44	0.91	96	36	2.22 (24.0)	1.4
WTE0960422	2.44	1.07	96	42	2.61 (28.0)	1.7
WTE0960482	2.44	1.22	96	48	2.98 (32.0)	2.0
WTE0960602	2.44	1.52	96	60	3.71 (40.0)	2.5
WTE1080242	2.74	0.61	108	24	1.67 (18.0)	1.0
WTE1080302	2.74	0.76	108	30	2.09 (22.5)	1.3
WTE1080362	2.74	0.91	108	36	2.51 (27.0)	1.6
WTE1080422	2.74	1.07	108	42	2.93 (31.5)	1.9
WTE1080482	2.74	1.22	108	48	3.34 (36.0)	2.2
WTE1080602	2.74	1.52	108	60	4.18 (45.0)	2.7
WTE1180242	3.0	0.61	118	24	1.85 (20.0)	1.2
WTE1180302	3.0	0.76	118	30	2.32 (25.0)	1.5
WTE1180362	3.0	0.91	118	36	2.74 (29.5)	1.8
WTE1180422	3.0	1.07	118	42	3.16 (34.0)	2.1
WTE1180482	3.0	1.22	118	48	3.62 (39.0)	2.3
WTE1180602	3.0	1.52	118	60	4.55 (49.0)	2.8

② 240 Vac custom mat configurations available. Contact EasyHeat.

PRODUCT SELECTION CHART

Warm Tiles Thermostat Kits

Model Number	Description	Voltage	Amps
FG	Non-programmable	120/240 Vac	15
FGS	Programmable for 7 or 5/2 days	120/240 Vac	15

WARNINGS

- Do not alter the length of the heating mat to suit a floor area larger or smaller than the recommended range for that mat.
- It is recommended that the circuit supplying the heating mat have ground fault protection; this is mandatory by electrical code for some applications in many regions.
- Carefully follow installation instructions provided with product.

TECHNICAL DATA

Voltage	120 or 240 volts
WTE Mat Thickness	3.2 mm (0.125 inch)
Standard Cold Lead Length	4.6 m (15 feet)
Maximum Cold Lead Length	10.7 m (35 feet)
Wattage	Up to 160 watts per square meter (Up to 15 watts per square foot)
Minimum Installation Temperature	0° C (32° F)
Minimum Area	0.6 square meter (6 square feet)
Maximum Area	11.1 square meter (120 square feet)
Maximum Current	10.7 amps

