

ASSOH – SONOMA™ HORIZON

WALL FAN HEATER



SONOMA™ HORIZON



THE CLASSIC FAN-HEATER OPTION

The Sonoma Horizon fan heater sets the bar high for optimal comfort. This quiet but fast heating solution is perfect for any room. Its impact-resistant facade makes it a safe and sustainable choice. Easy to install, the Sonoma Horizon fan heater gives your room a classic touch.

■ DESIGNED WITH THE USER EXPERIENCE IN MIND

CONTROLS LOCATED AT THE TOP OF THE UNIT

■ CAN BE INSTALLED HIGH UP OUT OF THE REACH OF CHILDREN AND PETS

■ COMPACT FIT ANYWHERE, PERFECT FOR SMALL SPACES

■ OPTIMAL SAFETY INTEGRATED THERMAL CUTOFF IMPACT-RESISTANT FACADE

■ FAST COMFORT RAPID TEMPERATURE RISE

■ QUIET FAN

COLOR

- white

FINISH

- epoxy-polyester powdercoat

MANUFACTURING

- 22-gauge steel cabinet and 20-gauge steel grille
- thermal protections with manual reset
- additional one-time thermal fuse

ELEMENT

- nichrome element produces instant heat

CONTROL

- built-in thermostat (optional)
- wall thermostat (not included) – the use of an electronic thermostat is strongly recommended

INSTALLATION

- recessed only
- bottom of the wall: 6 in. min. from floor
- top to the wall: 6 in. min. from ceiling

WARRANTY

- five years

IDEAL FOR:

hallway, lobby, living room, kitchen, bedroom, office

°STELPRO

Stelpro reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. No returns accepted on optional-color products. For all the latest models and prices, please refer to our website at www.stelpro.com.





TECHNICAL SPECIFICATIONS

WITHOUT CONTROL CODE	BUILT-IN THERMOSTAT CODE	VOLTAGE VOLTS	POWER*		HEIGHT IN.	LENGTH IN.	WEIGHT LB
			WATTS	BTU/H			
ASSOH1001WCW	ASSOH1001T2W	120	1000 or 500	3413 or 1706	9	12 9/16	7.3
ASSOH1008WCW	ASSOH1008T2W	208	1000 or 500	3413 or 1706	9	12 9/16	7.3
ASSOH1002WCW	ASSOH1002T2W	240/208	1000/750 or 500/375	3413/2560 or 1706/1280	9	12 9/16	7.3
ASSOH1501WCW	ASSOH1501T2W	120	1500 or 750	5119 or 2560	9	12 9/16	7.3
ASSOH1502WCW	ASSOH1502T2W	240/208	1500/1125 or 750/560	5119/3839 or 2560/1911	9	12 9/16	7.3
ASSOH2008WCW	ASSOH2008T2W	208	2000 or 1000	6825 or 3413	9	12 9/16	7.3
ASSOH2002WCW	ASSOH2002T2W	240/208	2000/1500 or 1000/750	6825/5119 or 3413/2560	9	12 9/16	7.3

Add WBB for unit without back box (available for U.S. market only).

*Choice of power at installation

ACCESSORIES

PRODUCT	DESCRIPTION
ASSOBB6	back box (6)

TECHNICAL DRAWINGS

