



Approved for wall or ceiling installation

Manufactured in U.S.A.

### Features

- Wattage selectable at time of installation.
- Models shipped wired to highest wattage.
- Approved for horizontal mounting - right or left discharge.
- Fan purge circuit.
- Disconnect switch.
- Drywall depth embossments on back can.
- 18 Gauge powder coated steel & extruded Aluminum front.
- Manual reset thermal limit.
- Steel block fin element.
- Propeller style fan blade: 1060 RPM motor; 100 CFM.
- Weight 6 lbs.
- Rough in dimensions: 9 1/4" Wide x 12 1/8" High x 3 5/8" Deep.
- Grill dimensions: 10" Wide x 13 1/8" High.

### Standard Models

UPC# 686334	MODEL	SELECTABLE INSTALLATION WATTAGE	MAX BTU's	VOLTS	MAX AMPS	LIST
<b>TAMPERPROOF IN-BUILT DOUBLE POLE THERMOSTAT (50° - 90° TEMPERATURE RANGE)</b>						
996211	E3055T2DWB	750 or 1500	5120	120	12.5	285
996228	E3058T2DWB	900 or 1800	6143	120	15.0	288
996259	F3052T2DWB	1000 or 2000	6826	208	8.3	
945691	F30522T2DWB	500 or 750 or 1000 or 1250 or 1500 or 1750 or 2250	7680	208	10.8	328
996280	H3052T2DWB	750 or 1000 - 1500 or 2000	6826	208 / 240	8.3	285
945721	H30522T2DWB	500 or 750 or 1000 or 1250 or 1500 or 1750 or 2250	7680	240	9.4	326
996310	G3052T2DWB	2000	6826	277	7.2	288
<b>TAMPERPROOF IN-BUILT SINGLE POLE THERMOSTAT (50° - 90° TEMPERATURE RANGE)</b>						
996068	E3055TDWB	750 or 1500	5120	120	12.5	267
996075	E3058TDWB	900 or 1800	6143	120	15.0	269
996105	F3052TDWB	1000 or 2000	6826	208	8.3	
945639	F30522TDWB	500 or 750 or 1000 or 1250 or 1500 or 1750 or 2250	7680	208	10.8	310
996136	H3052TDWB	750 or 1000 - 1500 or 2000	6826	208 / 240	8.3	267
945660	H30522TDWB	500 or 750 or 1000 or 1250 or 1500 or 1750 or 2250	7680	240	9.4	302
996167	G3052TDWB	2000	6826	277	7.2	269

### Accessories

UPC# 686334	MODEL	DESCRIPTION	LIST
996945	305EX8	1" EXTENDER	37
996938	305EX16	2" EXTENDER	38
996921	305EX32	4" SURFACE MOUNT FRAME	43

Note: Please see page 60 for custom color availability - add 10% to net heater cost.