

3000 Series Fan Forced Ceiling Heater



Manufactured in U.S.A.



Standard Models

WHITE		SELECTABLE INSTALLATION WATTAGE	MAX BTU'S	VOLTS	MAX AMPS	LIST
UPC#	MODEL					
686334						254
948821	E3035DWBW	750 or 1500	5120	120	13	
948838	E3038DWBW	900 or 1800	6143	120	15	
948883	H3032DWBW	750 or 1000 - 1500 or 2000	6826	208 / 240	8	
948906	G3032DWBW	2000	6826	277	7	

Selectable Wattages, Back Cans, And Power Disconnects

- Wattage selectable at time of installation - models shipped wired to highest Wattage
- Fan purge circuit (requires 2 wire control circuit when remote wall thermostat is used with the unit)
- Models may not be used with remote double pole thermostat
- Drywall depth embossments on back can
- Powder coated 18 Gauge steel front
- Manual reset thermal limit
- Steel block fin element
- Propeller style fan blade - 1060 RPM / 100 CFM
- Weight 6 lbs.
- Optional field installed control voltage relays available
- Rough in dimensions - 9 1/4" Wide - 12 1/8" High - 3 5/8" Deep
- Grill dimensions: 9 25/32" Wide - 13" High

Field Installed Accessories

UPC#	MODEL	DESCRIPTION	LIST
686334			
996846	30R	24 VOLT RELAY	35
996853	30R2	120 VOLT RELAY	
951500	30R8	208/240 VOLT RELAY	37
951494	30R7	277 VOLT RELAY	
996976	303EX8RW	1" EXTENDER	37
996969	303EX16RW	2" EXTENDER	38
996952	303EX32RW	4" SURFACE MOUNT FRAME	44
460033	TB3000	T-BAR FRAME	58

3380 Series Commercial Fan Forced Ceiling Heater

Product Specifications

Furnish and install Electric Forced Air Heaters, Series 3380 where specified. The heaters shall be constructed of a heavy gauge steel housing. The rough-in dimensions are 19-3/16" wide x 4" deep. The finish shall be baked-on powder coat in Ceiling White color. The units shall be available in ratings from 1500 through 4800 Watts with an optional factory installed single pole thermostat.

The heaters shall have a low speed 600-RPM motor, which drives a vane axial blower to deliver a quite 175 CFM's of down flow air. The heating element shall be of the block finned type with large, parallel steel fins for quick heat transfer. Unit shall have as standard, a manual reset capillary type limit control, for added safety. Unit weight 22 pounds.



Manufactured in U.S.A.

Features & Standard Models

Recess, Surface, Or "T" Bar Mounting



- Fan purge circuit (requires 2 wire control circuit when remote wall thermostat is used with the unit)
- Disconnect switch
- White powder coated 18 Gauge steel grill
- Manual reset thermal limit
- Steel block fin element
- Vane axial fan blade:
1.5KW - 4.0KW units: 700 RPM motor; 175 CFM
4.8KW units: 900 RPM motor; 200 CFM
- Rough in dimensions:
14 3/16" wide x 19 5/16" high x 4" deep
- Grill dimensions:
15 3/8" wide x 20 9/64" high
- Optional factory installed tamper resistant thermostat

UPC#	MODEL	KW	BTU'S	VOLTS	PH	AMPS	TEMP RISE	LIST	
686334									
366489	E3383D-RP	1.5	5120	120	1	12.5	27 °F	589	
366298	F3386D-RP	4.0	13600	208		19.2	72 °F	619	
366304	F3387D-RP	4.8	16382	208		23.1	76 °F	697	
366342	HF3384D-RP	2.0 / 1.5	6826/5120	240/208		8.3/7.2	36 °F	541	
366359	HF3385D-RP	3.0 / 2.3	10200/7679	240/208		12.5/10.8	54 °F	617	
366366	HF3386D-RP	4.0 / 3.0	13600/10200	240/208		16.8/14.4	72 °F		
366373	H3387D-RP	4.8	16382	240		20	76 °F	696	
366502	G3383D-RP	1.5	5120	277		5.4	27 °F	589	
366410	G3384D-RP	2.0	6826	277		7.2	36 °F	617	
366427	G3385D-RP	3.0	10200	277		10.8	54 °F	697	
366434	G3386D-RP	4.0	13600	277		14.4	72 °F		
366441	G3387D-RP	4.8	16382	277		17.3	76 °F	772	
International Models									
470889	M3384D-RPi	1680	5734	220		1	7.6	30 °F	589
470896	M3385D-RPi	2520	8600		11.5		50 °F	619	
470902	M3386D-RPi	4032	13761		18.3		72 °F	697	

Accessories

UPC	MODEL	DESCRIPTION	WT.	LIST
686334				
377850	BOX3310	Additional Back Can	10 lbs	96
381109	3380EX33	Surface Mounting Adapter	1 lb	85
460026	TB3380	2X2 T-Bar Mounting Kit	7 lbs	57
Thermostat- Add suffix T to model		Factory installed single pole, positive off. Range-60° F-105° F		111