

XtremeFLEX[®]

RKP Heating Tapes


with Preset Thermostat

NEW!



- ▶ **Extremely Flexible** 1/4" (6mm) minimum bend radius
- ▶ Plug-and-play
- ▶ Moisture and chemical resistant
- ▶ Built-in preset thermostat
- ▶ Lengths up to 200ft (61m)

Can Your Heat Trace Do This?



BriskHeat[®]

Your *Heating* Specialist since 1949

www.briskheat.com

XtremeFLEX[®]

RKP Heating Tapes

with Preset Thermostat



Specifications:

- Built-in controlling thermostat: 70°F or 120°F (21°C or 49°C)
- Lengths up to 200ft (61m)
- Moisture and chemical resistant
- Silicone rubber extruded construction
- Power density: 6W/ft (19.7W/m)
- Power cord: 5-foot (1.5m)
 - 120VAC includes standard 2-prong plug (NEMA 1-15)
 - 240VAC has crimped ferrule terminated leads
- Ingress Protection Rating: IP66
- Custom temperatures and lengths available



Ordering Information:

Width in (mm)	Length ft (m)	Total Watts	70°F (21°C) Thermostat		120°F (49°C) Thermostat	
			Part No. 120V	Part No. 240V	Part No. 120V	Part No. 240V
0.5 (13)	10 (3.0)	60	RKP1A0120	RKP2A0120	RKP1B0120	RKP2B0120
0.5 (13)	20 (6.1)	120	RKP1A0240	RKP2A0240	RKP1B0240	RKP2B0240
0.5 (13)	40 (12.2)	240	RKP1A0480	RKP2A0480	RKP1B0480	RKP2B0480
0.5 (13)	50 (15.2)	300	RKP1A0600	RKP2A0600	RKP1B0600	RKP2B0600
0.5 (13)	60 (18.3)	360	RKP1A0720	RKP2A0720	RKP1B0720	RKP2B0720
0.5 (13)	75 (22.9)	450	RKP1A0900	RKP2A0900	RKP1B0900	RKP2B0900
0.5 (13)	80 (24.4)	480	RKP1A0960	RKP2A0960	RKP1B0960	RKP2B0960
0.5 (13)	100 (30.5)	600	RKP1A1200	RKP2A1200	RKP1B1200	RKP2B1200
0.5 (13)	125 (38.1)	750	RKP1A1500	RKP2A1500	RKP1B1500	RKP2B1500
0.5 (13)	150 (45.7)	900	N/A	RKP2A1800	N/A	RKP2B1800
0.5 (13)	200 (61.0)	1200	N/A	RKP2A2400	N/A	RKP2B2400

Accessories:



Fiberglass Adhesive Tape (PN: PSAT36A)
 Size: 0.5" x 36yd (13mm x 38m)
 Maximum exposure temperature: 350°F (176°C)



GFCI adapter (PN: GFCI01)
 Converts a standard outlet into a GFCI protected outlet. For 120VAC use, max 15A.



INSUL-LOCK[®] DS Foam Insulation
 Premium insulation with adhesive flap. For pipe diameters ½"-4". Size: 6ft (1.8m) length.

Custom Sizes and Designs Available: Contact your local distributor or BriskHeat[®] for more information.